



12" man hole + primary shutt off valve. 14" stainless steel float ball.

20" Man hole for inspection

20-ton telescopic hoist cylinder

24' hydraulic boom. 270 deg. rotation. 8" flex hose. Pivot to ground level
Stainless Steel tube in center with quick connect.

Air actuated vacuum breaker + (2) 8" vacuum line.

(2) Carbon steel cyclone + drop box

6" Cam lock + Top opening door and elbow

420,000 btu water boiler. 12V
Heated aluminium cabinet for winter operations

HIBON 5250 cfm/ 27" Hg blower.
Direct drive via transfer case
(1) Exhaust, (1) Air intake.

Final filtration 10 microns cartridge (driver side)

(4) x 300 US Gallon plastic water tank. Total 1200 US Gallon
Heated line from engine Prestone (Winter package)

Ladder (retractable), cat walk
and safety harness attachment tube

Safety brace with LED light (Light up inside of tank)

Fully open hydraulic rear door

Flashing beacon + Arrow

(4) Hydraulic door lock

Hose hook

4" Brass decant manual valve

6" Brass discharged manual valve

6" Brass suction manual valve
+ 6" suction pipe with deflector

Aluminium Splash guard

Aluminium chute

Heavy duty bumper

Bush Hog plastic extensions + rack

Cone holder

3000 US Gallon (15 CY)
Carbon steel debris tank. Stainless steel liner

Hydraulic vibrator

(3) Aluminium tool box (LED light in all).
1 x tall cabinet on driver side beside cyclone (Heated with 12 Volt Glycol heater)
+ 1x large cabinet at the back of truck on driver side
+ 1 x large one on passenger side Under deck

MULTIPLEX color screen in stainless steel control box
21 fonctions wireless remote control with charging dock station

100 gal US Aluminium fuel tank. Driver side.

Load sense hydraulic system. Piston pump

Western Star 49X (2024). Cummins X15, Allison 4500RDS
Tandem / tandem SPIF 22 axle configuration

Fully insulated and heated aluminium water pump and boiler cabinet

Wabasto diesel fuel heater, 7000 btu for water pump and boiler cabinet

100' 3/8" diam hose + spring return hose reel

High pressure water pump (hydro excavation) 5800 psi/ 10 gpm.

Air purge system + Fully heated (GLYCOL) and insulated water lines for winter operation

5800 psi/ 10 gpm
5250 cfm/27Hg

HERCULES X